

Nummer: TD 006 EN

Datum: 11.11.2005



Revision:

Scale ice maker

HER 1500

Without compressor

HIGEL[®]
Kältetechnik



Technical Data

Refrigeration Engineering

Capacity (Kg/24h)	1500
Refrigeration power requirement	8000 W
Refrigerant	R404 A
Evaporation temp VT	- 23,3 C°
VT max.	- 25 C° !!!!!
Refrigeration unit possibility* (Outside temp.)	LH84/4CC-6.2Y → 32 °C

Electric

Power Supply (V)	3 x 380V+ N 50Hz
Power input (W)	150 W
Current consumption (A) Maxi	0,8 A
3	
4	
	24VAC / 24VDC

Mechanic

Volume (M³)	0,48
Weight	140 Kg

Connection

Water connection	
Inlet	R 3/4 "
Outlet	R 3/4 "
Cold connection	
Pressure pipe	3/4" UNF 12mm
Suction pipe	Lötfansch/Brazed flange 28mm

General

Schacht(Optional) BxTxH mm	
9	
Refrige.valve Y3	EVR6
Exp.valve (thermal)	
Exp.valve (pressure)	AEL6
Water pressure	1-- 6 Bars

Es ist empfehlenswert ein Wärmeaustauscher(Beispiel HE.X Danfoss) zu installieren. Dies verhindert den Rücklauf der Flüssigkeit zu dem Verdichter
Il est conseillé d'insérer un échangeur thermique(exemple: HE x Danfoss) afin d'éviter les retours de liquide vers le compresseur.
It's recommendable to installed a heat exchanger(example HE.x Danfoss).This prevents the return of the liquid to the compressor.
Рекомендуется установка теплообменника (напр. HE.X Danfoss). Он предохранит вытекание жидкости к испарителю.
Es recomendable instalar un intercambiador térmico(He x Danfoss) con el fin de evitar retornos de liquido hacia el compresor.